

BDS SUSPENSION

2015-2016 FORD F150 2WD



Vehicle Specs: 6" Lift Kit - 35" Cooper Discoverer STT - 20" Halo HE886



4" AND 6" DSC COILOVER SYSTEM

- FOX 2.5 Factory Series Coilover w/ DSC Adjusters
- One piece, high clearance, laser cut crossmembers
- Differential skidplate and offroad protection
- Improves on-road/off-road performance & handling
- FMVSS No.126 (ESC System) Compliant



FOX DSC ADJUSTER (DUAL SPEED COMPRESSION)

Adds 12-levels of high speed and 10-levels of low speed adjustment to dial in ride quality.



#1522FDSC - 6" kit w/ FOX 2.5 DSC Coilovers

2015-2016 FORD F150 2WD

LIFT & METHOD	QTY	PART#	DESCRIPTION	RECOMMENDED ACCESSORIES	NOTES	
2.5" Front / 0" Rear Upper Strut Mount Kit #572H 66FK641	1	013250	Front Leveling Kit	85651	Rear NX2 Shock (2 req'd) or FOX 2.0 Rear Gas Shock (2 req'd)	6
				98224651	1" Rear Block and U-Bolt	7
				013109		
4" Front / 4" Rear IFS w/ Strut Spacer Rear Block Kit Kit #1523H 24FK2161 FOX Performance C/O System Kit #1523F 87FK4333 FOX Performance DSC C/O System Kit #1523FDSC 87FK4563	1	023634	DS Knuckle	98224828	FOX 2.0 Rear Gas Shock (2 req'd)	1
	1	023635	PS Knuckle	023416	2" Rear Block	2
	1	023644	Front Box Kit	123018	E-brake Bracket	3
	1	013429	Rear Box Kit			4
	1	023404	Front Strut Spacer Kit or			5
	1	88302134	FOX 2.5 Coilover Kit or			
	1	88306134	FOX 2.5 DSC Coilover Kit			
	2	85828	Rear NX2 Shock or			
2	98224828	FOX 2.0 Rear Gas Shock				
6" Front / 5" Rear IFS w/ Strut Spacer Rear Block Kit Kit #1522H 01FK5261 FOX Performance C/O System Kit #1522F 05FK1443 FOX Performance DSC C/O System Kit #1522FDSC 87FK4563	1	023634	DS Knuckle	98224760	FOX 2.0 Rear Gas Shock (2 req'd)	1
	1	023635	PS Knuckle	013429	4" Rear Block	2
	1	023644	Front Box Kit	123018	E-brake Bracket	3
	1	013529	Rear Box Kit	122405	Carrier Bearing Drop Kit	4
	1	023605	Front Strut Spacer Kit or	123609	Rear Drive Shaft Spacer	5
	1	88302114	FOX 2.5 Coilover Kit or			
	1	88306114	FOX 2.5 DSC Coilover Kit			
	2	85760	Rear NX2 Shock or			
2	98224760	FOX 2.0 Rear Gas Shock				

Notes

1. 18" wheels with 5-5.5" total backspacing should be test fir prior to mounting tire to ensure proper clearance to BDS steering knuckle.
2. 18" or larger diameter wheels required. Stock 17" & 18" wheels cannot be reinstalled. Stock 20" wheels can be used with up to a 305/60-20 tires.
3. To achieve a level to tail low appearance on 6" kits use #013429 with Kit#s 1522H, 1522F, 1522FDSC. Block kits replace factory 1-1/4" block.
4. Models with a 2-piece rear driveshaft may require carrier bearing drop shim kit #122405
5. This kit is FMVSS No. 126 Compliant
6. Strut Compressor required for installation.
7. 1" Rear block kit is available in the accessories.



517-279-2135 | bds-suspension.com